ELAC Concentro S 503.2

The life of sound.



ELACConcentro S 503.2

The name Concentro signifies the extraordinary in every respect. The compact Concentro S 503.2 masterfully delivers the 'wow factor' from a surprisingly small package.



AS-XR technology

Unique, eye-catching, and acoustically ideal: the crystalline shape of the membrane provides the perfect balance of stiffness and damping.



Modern Hybrid Design

The progressive design elements from the Concentro Series combine with the clean lines of the Vela Series to create a strong visual presence.



StepX-JET

Since no two rooms are the same, midrange directivity can be adjusted using the exchangeable DCRs supplied.

Be in no doubt, the S 503.2 is a true Concentro in every respect. Design features and technical details that drove the success of the S 507 and S 509 are now combined in compact dimensions. The trapezoid basic shape, convex shaped baffle, and gently angled cabinet combine in a strikingly organic way to create a strong visual statement.

The extensive list of patented features and the revised woofer magnet system guarantee superlative sound. The effortless performance can be adjusted to suit the room acoustics. Close your eyes and you'll instantly forget you're listening to a compact speaker ... all you hear is music.

The Concentro S 503.2 is available in black and white high-gloss finishes and in high-gloss walnut veneer. The LS 100 stand specially developed for the Concentro S 503.2 is an available option.

Downloaded from www.linephaze.com

- Find specs, manuals and used listings across thousands of audio products.

ELAC Concentro S 503.2

CONCENTRO S 503.2

400 mm Height Width Depth 372 mm Weight 13.4 kg

Туре

Woofer 1 x 180 mm Ø, AS-XR cone Midrange 1 x 50 | 130 mm Ø, AS-XR AL

Tweeter

Crossover frequency 120 W | 200 W Nominal/peak power handling Minimum impedance

Peak power handling

Sensitivity

Suitable for amplifiers from ... to

Nominal impedance

Recommended amplifier power

Finishes

Accessories

225 mm

3-way, bass reflex

JET 6

400 | 2600 Hz

4.8 Ω bei 120 Hz

400 W

87 dB / 2.83 V / m

 $4 - 8 \Omega$ 4Ω

60 - 500 W / channel

High-Gloss Black Lacquer, High-Gloss White Lacquer High-Gloss

Walnut Veneer

Bi-Wiring-jumper set,

3 DCR (Directivity Control Ring)







Downloaded from www.linephaze.com

- Find specs, manuals and used listings across thousands of audio products.