



ANALOGUE & DIGITAL PREAMPLIFIER

MIMESIS SIGNATURE

AUDIO PURITY

Elevating the auditory experience to new heights, we proudly unveil the Mimesis Signature, a convergence of analogue finesse and digital prowess. This symphony of audio excellence introduces a paradigm shift in preamplification technology.

POWER SUPPLY

Nominal line voltage: 117 or 234 V (switchable)
 Fuse 2.5A for 110V
 Fuse 1A for 220V
 Input voltage range: +/- 10 %

ANALOGUE INPUTS

3 x pair RCA
 1 x pair XLR balanced

DIGITAL INPUTS

2 x Digital S/PDIF
 1 x Toslink Optical
 1 x USB AUDIO (up to 384 kHz PCM up to DSD512)

REAR PANEL CONNECTORS & CONTROLS

ON/OFF power switch key
 Voltage input selector
 RS232 Command connector

INPUT

Input impedance: 50 kOhms
 Nominal input level: 2.25 V RMS
 Maximum input level (unbalanced): 4V RMS
 Maximum input level (balanced): 2V RMS

OUTPUT

1 x pair of RCA
 1 x pair XLR balanced



ANALOGUE & DIGITAL PREAMPLIFIER

MIMESIS SIGNATURE

FREQUENCY RESPONSE

These values for any level to maximum output level

- +/- 0.1 dB, 10 Hz - 20 kHz
- +/- 1.5 dB, 10 Hz - 100 kHz
- +/- 3 dB, 10 Hz - 200 kHz

DISTORTION

With 1 V RMS output level, 80 KHz measurement bandwidth, 600 Ohms termination impedance

THD unbalanced in to unbalanced out < 0.005% (-90 dB) flat with frequency

IMD unbalanced in to unbalanced out < 0.002% (-80 dB)

NOISE

Signal-to noise ratio: > 120 dB at 0 dBFS

OPERATING TEMPERATURE

Room temperature: -30 to +40 degrees Celsius (-22 to +104 degrees Fahrenheit)

Internal temperature: +45 to +65 degrees Celsius (+113 to +149 degrees Fahrenheit)

SIZE & WEIGHT

44 W x 40 D x 13.2 H (cm) — 17.32 W x 15.75 D x 5.20 H (inch)

15 kg

COLOURS

Silver Grey