

# KEY FEATURES INCLUDE

- Linn 3K Driver Array creates a consistent single point
- High quality 6 1/2 inch Sandwich cone drive units deliver pitch accurate, musical bass
- Acoustically matched double-flared ports with unique "rifled" design
- Unique Linn loudspeaker configuration system allows simple alternation between Aktiv and passive configuration
- Akurate 226 bass reinforcement loudspeaker with servo-controlled amplification for exceptional bass reinforcement or extension

The Akurate range consists of four distinct acoustically matched loudspeakers that can be simply configured for high performance stereo and multi-channel music or home theatre applications.

The Akurate range has been designed to do full justice to the highest definition sound and vision formats, such as Studio Master downloads and Super Audio CD.

The full-range models, the 242, 225 and 212 loudspeakers, feature Linn's 3K Driver Array technology that creates a consistent single point sound source and improves high frequency response. All components used in the 3K Driver Array are tolerance matched to ensure sonic consistency throughout. Sandwich cone 6 ½ inch bass drive units deliver pure musical bass and the highly braced internal cabinet construction ensures the best possible performance from the advanced drive unit design.

The Akurate 226 bass reinforcement loudspeaker features servo-controlled Chakra amplification and digitally controlled signal processing for flexible configuration options. The 10 inch long-excursion drive unit is constantly monitored and regulated to maintain accurate and musical bass in any listening environment.

High grade real wood veneers are used through and are available in standard (American Cherry, Black Ash, Maple, Rosenut) or special high gloss finishes. Bespoke finishes can also be crafted to perfectly complement any living space.

### **AKURATE**

### **OVERVIEW**

A high performance multi-channel loudspeaker range







Downloaded from www.linephaze.com

- Find specs, manuals and used listings across thousands of audio products.

### **AKURATE**

### **TECHNICAL SPECIFICATION**

A high performance multi-channel loudspeaker range



#### **AKURATE 242**

5 way bass reflex floorstanding loudspeaker incorporating Linn 3K Driver Array and 2 x 6 1/2 inch Sandwich cone bass drivers

ı	Cabinet volume	42 litres
L	Impedance (passive)	8 Ω
1	Impedance (active bass)	16 Ω
1	Impedance (active mid)	8 Ω
1	Impedance (active tweeter)	6 Ω
1	Impedance	
	(active super tweeter)	4 Ω
1	Efficiency	87 dB for 1 watt at 1 metre (1 kHz)
1	Frequency response (passive)	49 Hz - 33 kHz
ı.	Frequency response (active)	40 Hz - 33 kHz
ı.	Magnetic shielding	yes
I.	Crossover options	Fully passive, partially or fully AKTIV
ı.	Connection options	Up to 5 way by wire or amplifier,
		bass lift option when Bi-wiring,
		+/- 2 dB

H 1000 x W 210 x D 380 mm H 39 1/2 x W 8 3/8 x D 15 inches

32 kg / 70 <sup>1</sup>/<sub>2</sub> lbs



#### **AKURATE 225**

5 way centre channel/dialogue loudspeaker incorporating Linn 3K Driver Array and 2 x 6 1/2 inch Sandwich cone bass drivers

Cabinet volume	25 litres
Impedance (passive)	8 Ω
Impedance (active bass)	16 Ω
Impedance (active mid)	8 Ω
Impedance (active tweeter)	6 Ω
Impedance	
(active super tweeter)	4 Ω
Efficiency	87 dB for 1 watt at 1 metre (1 kHz)
Frequency response (passive)	66 Hz - 33k Hz
Frequency response (active)	58 Hz - 33 kHz
Magnetic shielding	yes
Crossover options	Fully passive, partially or fully AKTIV
Connection options	Up to 5 way by wire or amplifier,
	bass lift option when Bi-wiring,
	+/- 2 dB
Dimensions	H 250 x W 600 x D 300 mm
	H 9 <sup>7</sup> /8 x W 23 <sup>3</sup> /4 D 12 inches
Weight	21 kg / 46 <sup>3</sup> / <sub>8</sub> lbs
	Impedance (passive) Impedance (active bass) Impedance (active mid) Impedance (active tweeter) Impedance (active super tweeter) Efficiency Frequency response (passive) Frequency response (active) Magnetic shielding Crossover options Connection options



#### **AKURATE 212**

Dimensions

Weight

4 way bass reflex compact loudspeaker incorporating Linn 3K Driver Array and 1 x 6 1/2 inch Sandwich cone bass driver



Dimensions

Weight

10 inch bass reinforcement loudspeaker with 500 W (RMS) of servo-controlled Chakra power amplification.

l	Cabinet volume	12 litres
	Impedance (passive)	8 Ω
	Impedance (active bass)	8 Ω
	Impedance (active mid)	8 Ω
	Impedance (active tweeter)	6 Ω
	Impedance	
	(active super tweeter)	4 Ω
	Efficiency	87 dB for 1 watt at 1 metre (1 kHz)
	Frequency response (passive)	70 Hz - 33 kHz
	Frequency response (active)	50 Hz - 33 kHz
	Magnetic shielding	yes
	Crossover options	Fully passive, partially or fully AKTIV
	Connection options	Up to 4 way by wire or amplifier
	Dimensions	H 350 x W 210 x D 300 mm
		H 14 x W 8 <sup>3</sup> / <sub>8</sub> x D 12 inches
	Weight	12 kg / 26 <sup>1</sup> / <sub>2</sub> lbs

1	Drive Unit	10 inch servo-controlled bass
1	Cabinet volume	26 litres
1	Mains input voltage	100 - 120 V
	(auto-sensing)	220 - 240 V
ı	Mains supply frequency	50 - 60 Hz
1	External frequency response	Adjustable from 10 Hz -235 Hz in 9 steps.
		Default is 10 Hz
1	High Pass Filtered	Adjustable from 55 Hz -130 Hz in 3 steps
	Output Frequency Response	and flat (to allow external low pass
		filtering). Default is 55 Hz
1	Gain	Adjustable in 1 dB steps
ı	Line input impedance	18 kΩ
1	Line output level	Electronically in parallel with line input
1	Output power	500 W RMS, 1000 W peak
1	Magnetic shielding	yes
1	Control features	Signal sensing, auto on/off
1	Protection	Fully protected against overload, over
		temperature, full short circuit and

overdrive

H 391 x W 360 x D 381 mm

H 15.4 x W 15 x D 14.1 inches

19 kg / 41 lbs 14 oz

The above information is subject to change without prior notice.

Linn Products Limited

Glasgow Road, Waterfoot, Eaglesham, Glasgow G76 0EQ, Scotland, UK. Telephone: +44 (0) 141 307 7777, Facsimile: +44 (0) 141 644 4262, Helpline: 0500 888909, E-mail: helpline@linn.co.uk, Website: www.linn.co.uk Linn Records Limited

Glasgow Road, Waterfoot, Eaglesham, Glasgow G76 0EQ, Scotland, UK.
Telephone: +44 (0) 141 303 5435, Facsimile: +44 (0) 141 303 5007, Helpline/Mail order: +44 (0) 141 303 5027, E-mail: info@linnrecords.com, Website: www.linnrecords.com

© 2009, Linn Products Limited. All rights reserved.

## Downloaded from www.linephaze.com

- Find specs, manuals and used listings across thousands of audio products.