

SPIRETM

FLOOR STANDING STEREO/HOME THEATER FRONT/SURROUND

25 YEARS OF PASSION, PRIDE AND PERFORMANCE

Revealing every subtle nuance of recorded sound with unflinching accuracy, Spire's ultra rigid AirFrame and curvilinear XStat electrostatic transducer achieve an effortless performance with precision, dynamics and three-dimensional sound staging. A PoweredForce active woofer system enables fine-tuning of the speaker's output in the frequency ranges most commonly and severely affected by room acoustics. The Spire is an extremely detailed electrostatic loudspeaker with bass that is not just deep and powerful, but also smooth, clean, and detailed.

Frequency Response 29–23,000 Hz ± 3dB Sensitivity 91 dB/2.83 volts/meter

Impedance 4 Ohms, 0.8 @ 20 kHz. Compatible with

4, 6, or 8 Ohm rated amplifiers.

Crossover Frequency 320 Hz

High/Mid Frequency Driver 44" x 11.3" (111.8 x 28.7 cm) CLS XStat

electrostatic (497 in²/3,209 cm²)

Low Frequency Driver 10" (25.4 cm) 200 watt PoweredForce

aluminum cone woofer

Recommended Amplifier Power 20–500 watts per channel

Weight 58 lbs. (26.3 kg) per channel

Dimensions (HxWxD) 59" x 12.5" x 17.75" (150 x 32 x 45.1 cm)

MARTIN LOGAN®

The Great American Speaker Company www.martinlogan.com

Application:

Stereo speaker or home theater front/ surround ideal for large and medium rooms.

Precision crossover engineering derived from the CLXTM loudspeaker perfectly blends high-resolution XStatTM and PoweredForceTM drivers providing an unparalleled sonic experience.

Key Features:

- CLS™ XStat electrostatic transducer
- Ultra rigid AirFrameTM
- 200 watt PoweredForce 10-inch aluminum cone woofer
- Precision built advanced topology VojtkoTM crossover
- 35Hz level control
- Custom ETC™ spikes

FINISH OPTIONS



ESL

SERIES











Visit configurator.martinlogan.com to explore the full range of finish options.



Downloaded from www.linephaze.com

- Find specs, manuals and used listings across thousands of audio products.