



Includes remote control



Smooth tray loading CD mechanism



Texas Instruments premium PCM5102A 32-bit/384kHz Digital to Analog Converter



12 volt trigger input



Coax output for use as a transport

The CD11MKII CD Player furthers Rotel's 30+ year legacy of delivering high performance, high value CD players.

The player's heavy steel chassis supports a proprietary Rotel disc transport exclusively for the playback of compact discs. The CD11MKII's smooth, tray-loading mechanism, precise laser pickup and silent running motor controller ensures seamless, worry-free playback of your CD collection.

Digital to Analog conversion is handled by a premium Texas Instruments PCM5102A 32-bit/384kHz DAC feeding custom-tuned digital low pass filter circuits. This sound-first design renders music on a large, open sound stage with exceptional details, precision, and finesse.

A linear power supply provides isolated outputs to the CD motor control circuit and critical audio circuits reducing noise and distortion presenting even the smallest of details from your CD collection.

Intuitive CD control functions on the front panel and included remote control ensure simple operation. The front panel graphic display shows playback status and disc meta data information including the title and artist.

The digital coaxial output allows the CD11MKII to be utilized as a Disc Transport. A rear panel 12V trigger input and RS232 connector allows seamless integration into even the most complex systems.

The CD11MKII is available in both black and silver colors.

## SPECIFICATION

|                                     |  |
|-------------------------------------|--|
| Total Harmonic Distortion + Noise   | 0.009% @ 1k Hz                               |
| Intermodulation Distortion          | 0.009% @ 1k Hz                               |
| Frequency Response ( $\pm 0.5$ dB)  | 20 - 20,000 Hz                               |
| Channel Balance                     | $\pm 0.5$ dB                                 |
| Phase Linearity                     | $\pm 0.5$ degree                             |
| Channel Separation                  | > 115 dB @ 10k Hz                            |
| Signal to Noise Ratio (A weighting) | > 125 dB                                     |
| Dynamic Range                       | > 99 dB                                      |
| Digital to Analog Converters        | Texas Instruments<br>PCM5102A 32-bit/384k Hz |
| Analog Output impedance             | 470 Ohms                                     |
| Digital Output                      | 0.5 V, Peak to Peak                          |
| Load Impedance                      | 75 Ohms                                      |
| Decodable Coaxial Digital Signals   | SPDIF LPCM<br>(up to 24-bit/192k Hz)         |



|                           |   |
|---------------------------|---|
| Power Requirements (AC)   |   |
| USA                       | 120 V, 60 Hz                                |
| Europe                    | 230 V, 50 Hz                                |
| Power Consumption         | 15 Watts                                    |
| Standby Power Consumption | < 0.5 Watts                                 |
| BTU                       | 40 BTU/h                                    |
| Dimensions (WxHxD)        | 430 x 98 x 314 mm<br>17" x 3 7/8" x 12 3/8" |
| Front Panel Height        | 80 mm / 3 1/8"                              |
| Weight (net)              | 6.2 kg, 13.7 lbs.                           |
| Finish                    | Black and Silver                            |

All specifications are accurate at the time of printing.  
Rotel reserves the right to make improvements without notice.