



P 1260 R – PRE-AMPLIFIER

Long ago, the legendary predecessor of this machine – the P 1230 R – wrote Hi-Fi history: it was selected by the specialist magazines as Hi-Fi device of the year so regularly that it was becoming rather monotonous. The device was so good, and so superior to the competition, that we built it for six years without making any modifications. However, now we have succeeded in improving it further by introducing the following new features: the latest generation of audio operational amplifiers (op-amps), which are so crucial in sound generation, are mounted on their own double-sided circuit board with power plane, voltage de-coupling and constant current by-pass. We call this sophisticated design feature OAD (Op Amp Decoupling), and it ensures that the op-amps have perfect conditions in which to work, guaranteeing unprecedented sound quality in conjunction with the High-End components. Seven line-level inputs, two with input buffers for other makes of machine with higher impedance (TV and Tape 2) and supplementary symmetrical outputs make the P 1260 R the perfect control centre of a High-End component system.



Specifications

<i>Frequency response (+0 -3 dB)</i>	0,5 Hz – 400 KHz
<i>Signal noise ratio</i>	
<i>High-level</i>	7 x 107 / 112 dB
<i>Phono MM (optional)</i>	83 / 87 dB
<i>Phono MC (optional)</i>	79 / 82 dB
<i>Subsonic Filter</i>	14 dB
<i>Total harmonic distortion</i>	< 0,001 %
<i>Intermodulation</i>	< 0,001 %
<i>Channel separation</i>	> 90 dB
<i>Input sensitivity nominal</i>	
<i>High-level</i>	250 mV / 20 kOhm
<i>Phono MM (optional)</i>	1 – 5 mV / 16 capacitances
<i>Phono MC (optional)</i>	60 – 1000 µV / 16 impedances
<i>Phono module replaced one high-level input</i>	
<i>Outputs</i>	
<i>Head phone</i>	50 Ohm
<i>2 x Tape</i>	250 mV / 100 Ohm
<i>PRE out Cinch nominal</i>	1 V eff
<i>maximal</i>	9,5 V eff
<i>Impedance</i>	22 Ohm
<i>PRE out XLR nominal</i>	1,45 V eff
<i>maximal</i>	19,6 V eff
<i>Impedance</i>	22 Ohm
<i>Surround interface (TASI)</i>	yes
<i>Reservoir capacity</i>	10000 µF
<i>Mains sockets 110 V or 230 V 50 Hz</i>	30 VA

<i>Dimensions (H x W x D)</i>	7,5 x 44 x 39 cm
<i>Weight</i>	7 kg
<i>Finishes</i>	silver aluminium, black
<i>Remote control</i>	incl. FM 100 R
<i>we reserve the right to alter technical specifications</i>	